THE CEMENT STORE®

IMPORTANT:

WHAT TYPE OF SEALER WAS APPLIED BEFORE?

If WATER-BASED sealer has been applied at any time in the past it must be completely removed before applying ANY new sealer.
RED LABEL WHITEOUT will remove old sealer.

SURFACE PREPARATION:

Once WATER-BASED sealer has been removed or if applying over SOLVENT-BASED sealer:

1. **Surface must be clean and free of dirt, debris, oil and contaminants.**
2. **Use TCS OILOUT oil spot remover as per directions. (if necessary)**
3. **Use TCS PINKPREP cleaner/degreaser as per directions.**
4. **Rinse entire area that is being sealed and give ample time (24 hours) to dry before applying new sealer.**
5. **Repair any scratches, peeling, white marks or blushing with RED LABEL WHITEOUT as per directions.**

CLEAN UP: Use a solvent like RED LABEL WHITEOUT to clean tools.

See our website for TIPS and further information

redlabelwhiteout.com

PRODUCT OF CANADA • 18.9 L / 5 Gallon

PRODUCT DESCRIPTION:

RED LABEL WHITEOUT is a proprietary blend of premium solvents for re-dissolving solvent based sealers to allow trapped moisture to dissipate, correct white out, peeling, delaminating, blushing, scratches and conditioning the surface for a new top coat. RED LABEL WHITEOUT will also strip WATER-BASED and SOLVENT-BASED sealer from concrete surfaces.

DIRECTIONS FOR USE:

- Follow SURFACE PREPARATION steps.
- Do not apply in wet weather or if rain is expected in 24 hours.
- DO NOT apply in DIRECT SUNLIGHT. (see YouTube videos)
- Apply product on a dry surface when air and surface temperatures are between 5°C-30°C and will remain between 5°C-30°C for at least 4 hours after applying.
- Apply generously with a solvent resistant sprayer (e.g. Chapin 1002 or 19069) or use a solvent resistant roller with a single lap motion only. **DO NOT OVER ROLL.**
- DO NOT pour directly from container onto surface. Always use a tray & a solvent resistant tray liner.
- Repeat if necessary until BLUSHING or WHITE SPOTS have disappeared.
- Reseal with BLACK LABEL HIGH GLOSS or GREEN LABEL SUPER GLOSS low VOC sealer.
- Spot treatments allow 4 hours before resealing.
- Full treatment allow 24 hours before resealing.

HIGHLY FLAMMABLE:

This product is extremely volatile. Extra precaution and care should be used when handling this product. Refrain from smoking when using the product. Use an efficient extractor fan if the product is applied in an enclosed area. Vapors may form an explosive mixture in the air.

STORAGE:

Keep container tightly closed when not in use. Keep away from heat from open flame. Keep out of reach of children. Do not freeze.

COVERAGE

Approx. 125-200 sq ft per gallon. Coverage varies due to porosity and condition of concrete surface.

RESIN SOLUTION. *flammable,* Class 3, UN 1866, PGII